

Pneumatic rock drills – pusher legs

Applications:

- Underground horizontal drilling

Features:

- High quality, designed for production drilling
- Single or double telescopic pusher legs



Pusher legs		BMT 51	ALF 71	ALF 71-1	ALF 72D	ALF 72D-1	BMK 62S
Telescope		Single	Single	Single	Single	Single	Single
Suitable for rock drill:		BBC 16W, 34W	BBC 16W, 34W	BBC 16W, 34W	BBD 94W	BBD 94W	RH 656W
Feeding length	mm	1300	1300	950	1300	1200	1300
Length retracted	mm	1658	1805	1455	1970	1830	1815
Length extracted	mm	2958	3105	2405	3270	3030	3115
Weight	kg	15	14	13	19	16	17
Cylinder Bore	mm	60	70	70	70	70	53
Part number		8321 0301 01	8321 0201 94	8321 0201 95	8321 0201 80	8321 0201 81	8321 0102 02

Data at 6 bar (90 psi) air pressure R=right rotation

Tampers

Our pneumatic tampers are your go-to tool for compacting jobs, even for tough soil types like clay. Lightweight and ergonomic, these powerful backfill tampers can be operated by a single person.

Applications:

- Compact soil around foundations and other structures
- Compacting backfill in trenches

Features:

- Maximum power – slow powerful blows efficiently and quickly compact all types of backfill, including clay and soils containing high percentages of finely crushed or powdered material
- Heat-treated cylinder and chrome plated piston significantly extend tool life
- Aluminum butt held with clamp screw for quick, easy replacement
- Exhaust deflector directs air, moisture and oil away from the operator
- Integral oiler for continuous lubrication

Tampers		TAM 14	TAM 19
Weight	kg	13,6	19
Length	mm	1320	1270
Body diameter	mm	71,4	98,4
Butt size	mm	127	158,8
Air consumption	l/s	8,4	13
impact frequency	bpm	800	780
Vibration level 3 axes (l SO 20643)	m/s ²	32,3	44,8
Sound pressure level (150 11203)	dB(A)	95	94
Hose connection	mm	12,7	19
Part number		8461 0250 14	8461 0250 15

