


SERVICE DATA


Tightening torques

Ref numbers match the drawing.



Socket spanner size 30

1. Treat the threads and threaded inserts for the fastening screws with an Anti-Seize agent.
2. Treat the surfaces between the fastening screw head, washer, and HP-accumulator cover with Anti-Seize.
3. Place on the HP-accumulator, and tighten the fastening screws by hand in a crosswise fashion.
4. Pretighten the fastening screws to 80 Nm (59 ft lbf), proceeding in a crosswise fashion,
5. then tighten each fastening screw through 30° in a crosswise fashion.
6. finally tighten each fastening screw again through 60° in a crosswise fashion.



Torque wrench or Power wrench size 75

1. Pretighten the tensioning bolts to 500 Nm (369 ft lbf), proceeding in a crosswise fashion,
2. then tighten each tensioning bolt through 180° (3 sides of hexagonal head) in a crosswise fashion,
3. finally tighten each tensioning bolt again through 120° (2 sides of hexagonal head) in a crosswise fashion.

Tightening torques

REF	DESCRIPTION	TORQUE	NOTES	REF	DESCRIPTION	TORQUE	NOTES
39	Allen Screw	85 Nm (63 ft lbf)	Allen key size 10	191	Tensioning Bolt		Torque wrench or Power wrench size 75
104	Allen Screw	380 Nm (280 ft lbf)	Allen key size 17	553	Allen Screw	85 Nm (63 ft lbf)	Allen key size 10
107	Threaded Plug	300 Nm (221 ft lbf)	Allen key size 22	561	Hydraulic Hose	42 Nm (31 ft lbf)	Open-ended wrench size 19
110	Threaded Plug	300 Nm (221 ft lbf)	Socket spanner size 24	562	Hydraulic Hose	16 Nm (12 ft lbf)	Open-ended wrench size 17
130	Non-Return Valve	200 Nm (148 ft lbf)	Jaw spanner size 41	564	Adapter	55 Nm (41 ft lbf)	Open-ended wrench size 19
139	Allen Screw	80 Nm (59 ft lbf)	Allen key size 10	565	Adapter	45 Nm (33 ft lbf)	Open-ended wrench size 19
150	Valve	250 Nm (184 ft lbf)	Allen key size 24	566	Fitting	60 Nm (44 ft lbf)	Open-ended wrench size 19, 22, 27
161	Fastening Screw		Socket spanner size 30	567	Fitting	55 Nm (41 ft lbf)	Open-ended wrench size 19, 22
181	Filling Valve	130 Nm (96 ft lbf)	Socket spanner size 22	568	Fitting	50 Nm (37 ft lbf)	Open-ended wrench size 17, 22, 27
182	Threaded Plug	20 Nm (15 ft lbf)	Allen key size 5	569	Fitting	45 Nm (33 ft lbf)	Open-ended wrench size 17, 19, 22
188	Threaded Plug	300 Nm (221 ft lbf)	Socket spanner size 24	587	Screw	22 Nm (16 ft lbf)	Security bit HATCON