

Impact Oil

## Safety Data Sheet

# Impact Oil

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**Product Code** 92340012 03  
**Infosafe No.** ACOHE IE/eng/C  
**Issued Date** 25/05/2007  
**Product Type/Use** Engine oil.

#### Supplier

Atlas Copco Construction Tools AB  
 SE-105 23  
 Stockholm  
 SWEDEN

#### Telephone Numbers

##### **Emergency Tel.**

+353 1 837 99 64

##### **Telephone/Fax Number**

Tel: +46 8 743 96 00

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### Preparation Description

Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

### 3. HAZARDS IDENTIFICATION

<b>EC Classification</b>	Not classified as Dangerous under EC criteria.
--------------------------	--

#### Human Health Hazards

No specific hazards under normal use conditions. Prolonged or repeated exposure may give rise to dermatitis. Used oil may contain harmful impurities.

#### Safety Hazards

Not classified as flammable, but will burn.

#### Environmental Hazards

Not classified as dangerous to the environment.

### 4. FIRST AID MEASURES

#### Symptoms and Effects

Not expected to give rise to an acute hazard under normal conditions of use.

#### Inhalation

In the unlikely event of dizziness or nausea, remove casualty to fresh air. If symptoms persist, obtain medical attention.

#### Skin

Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.

Impact Oil

### Eye

Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

### Ingestion

Wash out mouth with water and obtain medical attention. Do not induce vomiting.

### Advice to Doctor

Treat symptomatically. Aspiration into the lungs may result in chemical pneumonitis. Dermatitis may result from prolonged or repeated exposure. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.

## 5. FIRE FIGHTING MEASURES

### Specific Hazards

Combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide and unidentified organic and inorganic compounds.

### Extinguishing Media

Foam and dry chemical powder. Carbon dioxide, sand or earth may be used for small fires only.

### Unsuitable Extinguishing Media

Water in jet. Use of halon extinguishers should be avoided for environmental reasons.

### Protective Equipment

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Avoid contact with skin and eyes. Wear PVC, Neoprene or nitrile rubber gloves. Wear rubber knee length safety boots and PVC Jacket and Trousers. Wear safety glasses or full face shield if splashes are likely to occur.

### Environmental Precautions

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Inform local authorities if this cannot be prevented.

### Clean-up Methods - Small Spillages

Absorb liquid with sand or earth. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

### Clean-up Methods - Large Spillages

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

## 7. HANDLING AND STORAGE

### Handling

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Avoid prolonged or repeated contact with skin. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Cloth, paper and other materials that are used to absorb spills present a fire hazard. Avoid their accumulation by disposing of them safely and immediately. In addition to any specific recommendations given for controls of risks to health, safety and the environment, an assessment of risks must be made to help determine controls appropriate to local circumstances.

### Storage

Keep in a cool, dry, well-ventilated place. Use properly labelled and closeable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

### Storage Temperatures

0°C Minimum. 50°C Maximum.

Impact Oil

**Recommended Materials**

For containers or container linings, use mild steel or high density polyethylene.

**Unsuitable Materials**

For containers or container linings, avoid PVC.

**Other Information**

Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

**Exposure Limits**

Substance	Regulations	Exposure Duration	Exposure Limit	Units	Notes
Oil mist, mineral	EH 40 2005	TWA	5	mg/m <sup>3</sup>	
	EH 40 2005	STEL	10	mg/m <sup>3</sup>	

EH 40 2005

EH 40 2005 Health and Safety Executive. EH40; Workplace Exposure Limits

**Exposure Controls**

The choice of personal protective equipment is highly dependent upon local conditions, e.g. exposure to other chemical substances and micro-organisms, thermal hazards (protection from extremes of cold and heat), electrical hazards, mechanical hazards and appropriate degree of manual dexterity required to undertake an activity.

Whilst the content of this section may inform the choice of personal protective equipment used, the limitations of any information which can be provided must be fully understood, e.g. personal protective equipment chosen to protect employees from occasional splashes maybe entirely inadequate for activities involving partial or complete immersion. If the levels of oil mist or vapour in air are likely to exceed the occupational exposure standards then consideration should be given to the use of local exhaust ventilation to reduce personal exposure.

The choice of personal protective equipment should only be undertaken in the light of a full risk assessment by a suitably qualified competent person ( e.g. a professionally qualified occupational hygienist).

Effective protection is only achieved by correctly fitting and well maintained equipment and employers should ensure that appropriate training is given. All personal protective equipment should be regularly inspected and replaced if defective.

**Respiratory Protection**

At standard temperature and pressure, the Occupational Exposure Standard for oil vapour is unlikely to be exceeded. Care should be taken to keep exposures below applicable occupational exposure limits. If this cannot be achieved, use of a respirator fitted with an organic vapour cartridge combined with a particulate pre-filter should be considered. Half masks (EN 149) or valved half masks (EN 405) in combination with type A2 (EN 141) and P2/3 (EN 143) pre-filters may be considered.

**Hand Protection**

Chemical protective gloves are made from a wide range of materials, but there is no single glove material ( or combination of materials) which gives unlimited resistance to any individual or combination of substances or preparations. The extent of the breakthrough time will be affected by a combination of factors which include permeation, penetration, degradation, use pattern ( full immersion, occasional contacts) and how the glove is stored when not in use.

Theoretical maximum levels of protection are seldom achieved in practice and the actual level of protection can be difficult to assess. Nitrile gloves may offer relatively long breakthrough times and slow permeation rates. Test data, e.g breakthrough data obtained through test standard EN374-3:1994 are available from reputable equipment suppliers.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. A non perfumed moisturiser should be applied.

**Eye Protection**

Goggles conforming to a minimum standard of EN 166 345B should be considered if there is a possibility of eye contact with the product through splashing. Higher rated eye protection must be considered for highly hazardous operations or work areas. For example, employees involved in metalworking operations such as chipping, grinding or cutting may require additional protection to avert injury from fast moving particles or broken tools.

Impact Oil

**Body Protection**

Minimise all forms of skin contact. Overalls and shoes with oil resistant soles should be worn. Launder overalls and undergarments regularly.

**Environmental Exposure Controls**

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Colour</b>	Amber.
<b>Physical State</b>	Liquid at ambient temperature.
<b>Odour</b>	Characteristic mineral oil.
<b>pH Value</b>	Data not available.
<b>Vapour Pressure</b>	Expected to be less than 0.5 Pa at 20°C.
<b>Initial Boiling Point</b>	Expected to be above 280°C.
<b>Solubility in Water</b>	Negligible.
<b>Density</b>	circa 890 kg/m <sup>3</sup> at 15°C.
<b>Flash Point</b>	circa 240°C (COC).
<b>Flammable Limits - Upper</b>	10%(V/V) (typical).
<b>Flammable Limits - Lower</b>	1%(V/V) (typical).
<b>Auto-Ignition Temperature</b>	Expected to be above 320°C.
<b>Kinematic Viscosity</b>	circa 120 mm <sup>2</sup> /s at 40°C.
<b>Evaporation Rate</b>	Data not available.
<b>Vapour Density (Air=1)</b>	Greater than 1.
<b>Partition co-efficient, n-octanol/water</b>	Log Pow expected to be greater than 6.
<b>Pour Point</b>	circa -20°C.

## 10. STABILITY AND REACTIVITY

**Stability**

Stable.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Materials to Avoid**

Strong oxidizing agents.

**Hazardous Decomposition Products**

Hazardous decomposition products are not expected to form during normal storage.

## 11. TOXICOLOGICAL INFORMATION

**Basis for Assessment**

Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products.

**Acute Toxicity - Oral**

LD50 expected to be > 2000 mg/kg.

**Acute Toxicity - Dermal**

LD50 expected to be > 2000 mg/kg.

**Acute Toxicity - Inhalation**

Not considered to be an inhalation hazard under normal conditions of use.

**Eye Irritation**

Expected to be slightly irritating.

Impact Oil

**Skin Irritation**

Expected to be slightly irritating.

**Respiratory Irritation**

If mists are inhaled, slight irritation of the respiratory tract may occur.

**Skin Sensitisation**

Not expected to be a skin sensitizer.

**Carcinogenicity**

Product is based on mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Other components are not known to be associated with carcinogenic effects.

**Mutagenicity**

Not considered to be a mutagenic hazard.

**Reproductive Toxicity**

Not considered to be toxic to reproduction.

**Other Information**

Prolonged and/or repeated contact with products containing mineral oils may result in defatting of the skin, particularly at elevated temperatures. This may lead to irritation and possibly dermatitis, especially under conditions of poor personal hygiene. Skin contact should be minimised. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed. Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. It is prudent to assume that prolonged or repeated exposure to used engine oils may cause skin cancer.

## 12. ECOLOGICAL INFORMATION

**Basis for Assessment**

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

**Mobility**

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

**Persistence / Degradability**

Not expected to be readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

**Bioaccumulation**

Contains components with the potential to bioaccumulate.

**Ecotoxicity**

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Product is expected to be practically non-toxic to aquatic organisms, LL/EL50 >100 mg/l. (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

**Other Adverse Effects**

Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal**

Recycle or dispose of in accordance with prevailing regulations, by a recognised collector or contractor. The competence of the contractor to deal satisfactorily with this type of product should be established beforehand.

Impact Oil

Do not pollute the soil, water or environment with the waste product.

**Product Disposal**

As for waste disposal.

**Container Disposal**

Recycle or dispose of in accordance with the legislation in force with a recognised collector or contractor.

## 14. TRANSPORT INFORMATION

**Transport Information**

Not dangerous for transport under ADR/RID, IMO and IATA/ICAO regulations.

**ADR/RID Class**

None Allocated

**ADR/RID Packing Group**

None Allocated

**IMDG Hazard Class**

None Allocated

**IMDG Packing Group**

None Allocated

**IATA Hazard Class**

None Allocated

**IATA Packing Group**

None Allocated

## 15. REGULATORY INFORMATION

EC Symbols	None.
EC Risk Phrase	Not classified.
EC Safety Phrase	Not classified.
EINECS	All components listed or polymer exempt.
TSCA (USA)	All components listed.

**National Legislation**

Carriage of Dangerous Goods by Road Regulations 2001

EC (Classification, Packaging, Labelling and Notification of Dangerous Substances) Regulations 2000

EC (Classification, Packaging, Labelling and Notification of Dangerous Preparations) (Amendment) Regulations, 1998

Safety, Health and Welfare at Work (Chemical Agents) Regulations, 2001

**Packaging & Labelling**

Safety data sheet available for professional user on request.

## 16. OTHER INFORMATION

**Restrictions**

This product must not be used in applications other than recommended without first seeking the advice of the Atlas Copco technical department.

**Further Information**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It does not constitute a guarantee for any specific property of the product.

... **End Of SDS** ...