# **Material Safety Data Sheet**



# 1. Product and company Identification

Product name

Optimol Paste White T

MSDS#

453853

Code

453863-DE03

Product use

Paste

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer

Castrol Industrial North America, Inc.

150 W. Werrenville Road Naperville, IL 60563

Supplier

Castrol Industrial North America, Inc.

150 W. Warrenville Road Naperville, IL 60563

Descript Informations 4.8

Product Information: 1-800-621-2661

EMERGENCY SPILL

INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

#### 2. Hazards Identification

Physical state

Liquid. [Paste]

Color

White.

Emergency overview

WARNING !

CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Prolonged or repeated contact can defat the skin and lead to irritation end/or dermetitis. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry

Dermal contact. Eye contact. Inhalation, Ingestion,

Potential health effects

Eves

Causes eye initation.

Skin

Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis.

Inhalation

May cause respiratory tract irritation.

Ingestion

No known significant effects or critical hazards.

See toxicological information (section 11)

# 3. Composition/information on ingredients

Ingredient name	CAS #	%
Base oil - highly refined	Varles	30 - 35
kaolin	1332-58-7	5-10
Zinc oxide	1314-13-2	5 - 10
Fatty amide derivative.	Proprietary	1 - 5
titanium dioxide	13463-67-7	1-5

Product name	Optimol Paste \	White T	P	roduct code	453853-DE03	Page: 1/7
Version 1	Date of Issue	06/24/2009.	Format U	s	Language	ENGLISH.
			(U	JS)		(ENGLISH)

### 4. First aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention.

Skin contact

Immediately wash exposed skin with soap and water. Remove contaminated dothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. Get medical attention,

### 5. Fire-fighting measures

Flash point

Closed cup; >220°C (>428°F)

Fire/explosion hazards

In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable

Use an extinguishing agent suitable for the surrounding fire.

Not suitable

Do not use water jet.

Fire-fighting procedures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion

products

Combustion products may include the following:

phosphorus oxides metal oxide/exides

carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO2 etc.)

Protective clothing (fire)

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

#### 6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnal from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, alrhome exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small apill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if watersoluble or absorb with an linert dry material and place in an appropriate waste disposal container.

Dispose of via a licensed waste disposal contractor.

	Product name	Optimol Paste \	White T		Product code	453853-DE03	Page: 2/7
***************************************		Date of Issue		Format	US	Language	ENGLISH.
Management					(US)		(ENGLISH)

# 7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and wellventileted area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Exposure controls/personal protection

### Occupational exposure limits

Ingredient name

Occupational exposure limits

Base oil - highly refined

ACGIH (United States),

STEL: 10 mg/mº 15 minute(s). Form: Mineral oil, mist TWA: 5 mg/m\* 8 hour(s). Form: Mineral oil, mist OSHA (United States).

TWA: 5 mg/m² 8 hour(s), Form: Mineral oil, mist

kaolin

ACGIH TLV (United States).

TWA: 2 mg/m² 8 hour(s). Issued/Revised: 5/1996 Form: Respirable fraction

NIOSH REL (United States).

TWA: 5 mg/m² 10 hour(s). Issued/Revised: 6/1994 Form; Respirable fraction

TWA: 10 mg/m² 10 hour(s), Issued/Revised: 6/1894 Form; Total

OSHA PEL (United States).

TWA: 5 mg/mº 8 hour(s). Issued/Revised: 5/1993 Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Issued/Revised: 5/1993 Form: Total dust

Zinc oxide

ACGIH TLV (United States).

TWA: 2 mg/m\* 8 hour(s), issued/Revised; 1/2003 STEL: 10 mg/m³ 15 minute(s), Issued/Revised: 1/2003 NIOSH REL (United States).

CEIL: 15 mg/m² issued/Revised: 6/1994 Form: Dust

TWA: 5 mg/m² 10 hour(s), Issued/Revised: 6/1994 Form: Dust and fumes STEL: 10 mg/m3 15 minute(s), Issued/Revised: 6/1994 Form; Furne

OSHA PEL (United States).

TWA: 5 mg/m² 8 hour(s). Issued/Revised: 6/1993 Form: Furne

TWA: 5 mg/rm\* 8 hour(s). Issued/Revised: 6/1993 Form: Respirable fraction

TWA: 15 mg/m² 8 hour(s), issued/Revised: 6/1993 Form: Total dust

titanium dioxide

ACGIH TLV (United States).

TWA: 10 mg/m\* 8 hour(s), Issued/Revised: 5/1996

OSHA PEL (United States).

TWA: 15 mg/m<sup>4</sup> 8 hour(s), Issued/Revised: 6/1983 Form: Total dust

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures

Use only with adequate ventiletion. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Hydiane measures

.Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

rousing.

Personal protection

Eves

Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body

Do not get on skin or clothing. Wear suitable protective clothing.

Respiratory

Use adequate ventilation. Do not breathe vapor or mist,

Product name Opt	noi Paste White T	
------------------	-------------------	--

Product code

453853-DE03

Page: 3/7

Version 1

Date of issue 06/24/2009.

Format US

Language ENGLISH,

(US)

CROWDER SUPPLY CO, INC. - 8495 ROSLYN ST. - COMMERCE CITY, CO 80022 - TOLL FREE 888-883-5144 - www.crowdersupply.com

Hands

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# 9. Physical and chemical properties

Physical state

Paste

Color

White.

Odor

Mild.

Flash point

Closed cup: >220°C (>428°F)

Dansity

>1000 kg/m3 (>1 g/cm3) at 20°C

Vapor pressure

<0.01 kPa (<0.075 mm Hg) at 20°C

Solubility

Very slightly soluble in water

# 10. Stability and reactivity

Stability and reactivity

The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

Not aveilable.

Incompatibility with

various substances

Reactive or incompetible with the following materials: oxidizing materials.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

Hazardous polymerization

Under normal conditions of storage and use, hazardous polymerization will not occur.

# 11. Toxicological information

#### Classification

Product/ingredient name

MARC

NTP

OSHA

titenium dioxide

2₿

IARC:

2B - Possible carcinogen to human.

Other information

Potential chronic health effects

Carcinoganicity

Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

### 12. Ecological Information

#### Ecotoxicity

No testing has been performed by the manufacturer.

Persistence/degradability

Inherently biodegradable

Mobility

Non-volatile. Grease. Very slightly soluble in water.

Product name Optimol Paste White T

Product code

453853-DE03

Page: 4/7

Version 1

Date of Issue 06/24/2009,

Format US

Language ENGLISH.

(US)

# 13. Disposal considerations

Waste Information

The generation of waste should be evoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

## 14. Transport information

International transport regulations

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional Information
DOT Classification	Not regulated.	-	-	HE.	i te
TDG Classification	Not regulated.	-	*	-	-
IMDG Classific⊾ on	UN3077	Environmentally hazardous substance, solid, n.o.s. (Zinc oxids). Marine pollutant	9	111	Emergency schedules (EmS) F-A, S-F Marine pollutant
IATA/ICAO Classification	UN3077	Environmentally hazardous substance, solid, n.o.s. (Zinc oxide)	9	111	-

# 15. Regulatory information

### U.S. Federal Regulations

United States inventory (TSCA 8b)

At least one component is not listed.

TSCA 12(b) annual export notification: Mercury

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification; No products were found. SARA 302/304/311/312 hazardous chemicals: kaolin; titanium dioxide; Zinc oxide

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Optimol Paste

White T: Immediate (scute) health hezard

SARA 313

Product name CAS number Concentration

Form R - Reporting Zinc oxide 1314-13-2 4.99 - 5

requirements

Supplier notification Zinc oxide 1314-19-2 4.99 - 5

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4): CERCLA: Hazardous substances.: Antimony powder, 5000 lbs. (2270 kg); Arsenic: 1 lb. (0.454 kg); Cadmium; 10 lbs. (4.54 kg); lead: 10 lbs. (4.54 kg); Mercury: 1 lb. (0.454 kg); selenium; 100 lbs. (45.4 kg); Zinc powder - zinc dust (stabilized): 1000 lbs. (454 kg); Zinc oxide;

Product name Optimal Paste White T Product code 453853-DE03 Page: 5/7

Version 1 Date of issue 06/24/2009. Format US Language ENGLISH.

(US) (ENGLISH)

### State regulations

Massachusetts Substances

The following components are listed: ZINC OXIDE FUME; kaolin; TITANIUM DIOXIDE

New Jersey Hazardous

Substances

The following components are listed: ZINC OXIDE; TITANIUM DIOXIDE

Pennsylvania RTK Hazardous Substances

The following components are listed: ZINC DXIDE (ZNO); KAOLIN; TITANIUM OXIDE (TIO2)

California Prop. 65

WARNING: This product contains a chamical known to the State of California to cause cancer.

Arsenic

WARNING: This product contains a chemical known to the State of California to cause birth

defects or other reproductive harm.

Mercury

WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

Cadmium; lead

inventories

Canada Inventory

At least one component is not listed,

**Europe Inventory** 

All components are listed or exempted.

Australia inventory (AICS)

At least one component is not listed.

China inventory (IECSC) Japan inventory (ENCS)

At least one component is not listed. At least one component is not listed.

Korea inventory (KECI)

At least one component is not listed.

Philippines inventory

(PICCS)

At least one component is not listed.

### 16. Other information

Label requirements

WARNING 1

CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS@ Rating :

Health

National Fire

Protection

Association (U.S.A.)

Flammability 1

Physical Hazard

Personal

protection

History

Date of issue

06/24/2009,

Date of previous issue

No previous validation.

Prepared by

Product Stewardship

Notice to reader

Product name Optimol Paste White T

Product code

453853-DE03

Health

Page: 6/7

Fire hazard

instability

Specific hazard

Version 1 Date of issue 06/24/2009.

Format US

Language ENGLISH.

(US)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us,

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hezards inherent in the nature of the meterial. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hezards described in this sheet and of any precautions that should be taken.

Product name Optimal Paste White T

Product code

453853-DE03

Page: 7/7

Version 1 Date of issue 06/24/2009.

Format US

Language ENGLISH.

(US)