

PNEU-LIGHT



S P E C I F I C A T I O N S

PART #	LENGTH	LENGTH w/BRACKET	WIDTH	WIDTH w/BRACKET	WEIGHT	MINIMUM HOSE SIZE
TX-PL5500	7.0" 178 mm	11.5" 292 mm	8.5" 216 mm	11.0" 279 mm	25.55 lbs 11.6 kg	1/2" 13 mm

~ Made in U.S.A. ~

www.airtools.com

Email: tptinfo@airtools.com

TEXAS
1-800-231-9740
254-587-2533 (Int'l calls)

NEVADA
1-800-858-1222

VIRGINIA
1-800-626-1091

MICHIGAN
1-877-575-5733

 FUNCTIONAL SPECIFICATIONS

AIR PRESURE	VOLTS	AMPS	LUMENS	AIR COMSUMPTION	DECIBEL LEVEL
120 psi 8.3 Bar	13.1	5.0	6,025	13.1 cfm 371 l/min	60
110 psi 7.6 Bar	12.7	4.8	5,410	12.0 cfm 340 l/min	48
100 psi 6.9 Bar	12.3	4.3	4,725	11.5 cfm 326 l/min	<40
90 psi 6.2 Bar	11.8	3.7	4,165	9.8 cfm 278 l/min	<40
80 psi 5.5 Bar	11.3	3.1	3,417	8.5 cfm 241 l/min	<40
70 psi 4.8 Bar	10.7	2.5	2,889	6.8 cfm 193 l/min	<40
60 psi * 4.1 Bar	9.9	1.8	1,804	5.1 cfm 144 l/min	<40
50 psi 3.5 Bar	9.3	1.2	1,055	3.3 cfm 93 l/min	<40
40 psi 2.8 Bar	8.4	0.5	430	1.5 cfm 43 l/min	<40

* Minimum Pressure to Start

Features:

- ◆ Intrinsically Safe
- ◆ Compressed Air Driven
- ◆ LED Life Expectancy – 10,000 Hours
- ◆ T6 - Aircraft Grade Aluminum Housing
- ◆ Can Operate at a Large Range of Air Pressures
- ◆ Extremely Reliable Design
- ◆ Sealed Bearings For Extended Life
- ◆ Floodlight Pattern for Maximum Visibility
- ◆ Apex certification applied for